

UTA-10

GaN III Universal Travel Adapter with
2x USB-C® PD 140W, 1x USB-C® PD 18W,
1x USB-A 18W



GaN III charging technology



Charge 5 devices at once



Compact design



World-to-World adapter

Charge around the world

The Verbatim GaN III Universal Travel Adapter UTA-10 is a compact and versatile solution for travelers. It supports over 180 countries, offering EU, UK, US, Australia, and China plug options. Utilizing advanced GaN III technology, it's more efficient and compact.

This 5-in-1 adapter allows simultaneous charging of five devices through AC and USB ports, including two USB-C with Power Delivery 3.0 (with PPS support), Quick Charge 4+ output, up to 140W each, and USB-A port supports Quick Charge 3.0 output, up to 18W.

Ideal for international travel, this adapter ensures you gives you 100% peace of mind wherever you may go.

UTA-10

GaN III Universal Travel Adapter with
 2x USB-C® PD 140W, 1x USB-C® PD 18W,
 1x USB-A 18W

PN	Description	Bar Code	EAN128 Code	EAN14 Code
32125	Verbatim UTA- 10 GaN III Universal Travel Adapter 2x USB-C PD 3.1 140W 1x USB-C PD 18W 1x USB-A QC 3.0 18W	023942321255	(02)00023942321255(37)20(91)489	50023942321250

General Information

Input Plug Formats	Type A / B / C / E / F / G / I / J / L / N
Output Plug Formats	EU, UK, USA/Japan, AUS/China Type A / B / C / D / E / F / G / H / I / J / K / L / M / N / O
Material	Fire-proof polycarbonate, Copper (Pouch: Nylon + PVC)
Product Dimensions WxHxD (mm)	93.1 x 53.4 x 55.3
Product Weight (grams) approx	264
Colour	Black
Safety shutter	Yes, can only be opened with force of more than 75N (7.5Kg) per hole

Power

AC Input	100-250V, 50-60Hz
Rating	100-250V, 10A Max, 2500W Max
Total DC Output	140W
Earthed Plug	No
Fuse	10A, 250V (spare fuse included)
Fuse Compliance	BS1362
Charging Technology	PD3.1, PD3.0, QC4+, QC 3.0, FCP, SCP, AFC, PPS, BC1-2 and more.

Single Port Output

USB-C1 PD 3.1 & QC 4+ (PPS supported)	3.3-11V=5A, 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A, 28V = 5A 140W max.
USB-C2 PD 3.1 & QC 4+ (PPS supported)	3.3-11V=5A, 5V=3A, 9V=3A, 12V=3A, 15V=3A, 20V=5A, 28V = 5A 140W max.
USB-C3 QC 3.0	5V = 2.4 A, 9V = 2 A, 12V = 1.5 A 18W max.
USB-A1	5V = 2.4 A, 9V = 2 A, 12V = 1.5 A 18W max.

Multiport Max Output	USB-C1	USB-C2	USB-C3	USB-A1
USB-C1+USB-C2	100W	35W	-	-
USB-C1+USB-C3	100W	-	18W	-
USB-C1+USB-A1	100W	-	-	18W
USB-C2+USB-C3	-	100W	18W	-
USB-C2+USB-A1	-	100W	-	18W
USB-C3+USB-A1			12W	
USB-C1+USB-C2+USB-C3	65W	35W	18W	
USB-C1+USB-C2+USB-A1	65W	35W	-	18W
USB-C1+USB-C3+USB-A1	100W	-	12W	
USB-C2+USB-C3+USB-A1	-	100W	12W	
USB-C1+USB-C2+USB-C3+USB-A1	65W	35W	12W	

UTA-10

GaN III Universal Travel Adapter with
2x USB-C® PD 140W, 1x USB-C® PD 18W,
1x USB-A 18W

Other Features

Indoor use	Yes
Outdoor use	No
LED Indicators	Yes
Protective Functions	Safety shutter for child protection; can only be opened with force of more than 75N (7.5Kg) per hole
Compliance	EN 55032:2005/A11:2020 EN 55035:2017/A11:2020 EN IEC61000-3-2: 2019/A1:2021 EN 61000-3-3: 2013/A1:2019 EN IEC 62638-1:2020+A11:2020
ROHS Directive	2011/65/EC
Electromagnetic Compatibility	2014/30/EC
General product Safety	2001/95/EC

Storage and Operating Conditions

Storage Temperature	-20°C to 85°C
Operating Temperature	0°C to 25°C
Operating Humidity	25% to 90% RH

Logistic Information

Pack Dimensions LxWxH	90.6 x 62.7 x 105.6 mm (132 mm with hanger)
Pack Weight	242 g
Pcs per Pack	1
Outer Cartons Dimensions	330 x 230 x 200 mm
Outer Cartons Weight	5 340 g
Pcs per Outer Carton	20
Outer Carton per Layer	15
Layers per Pallet	6
Pcs per Pallet	1 800



UTA-10

GaN III Universal Travel Adapter with
2x USB-C® PD 140W, 1x USB-C® PD 18W,
1x USB-A 18W



Front



Back



Right angled UK plug



Right angled EU plug



Left angled USB



Right angled USB



Packaging 3D

Pack Contents:

- GaN III Universal Travel Adapter
- Travel pouch
- Quick Start Guide

Warranty

- 2 Year Limited Warranty

Warning

- THIS IS NOT A VOLTAGE CONVERTER
- FOR INDOOR USE ONLY
- NO GROUNDING: THIS PRODUCT IS FOR USE WITH UNEARTHED OR DOUBLE INSULATED APPLIANCES ONLY